

AutoCommand OEM® Feature Comparison

Features	25622	28623TN	28624TN	20095
Transmitter				
Number of transmitters		2	2	One 2-way and one 1-way
# of buttons on a transmitter		3	5	2-way - 5 buttons 1-way - 4 buttons
Range up to 1,000 ft		x	x	x
Anti-scan technology prevents code grabbing		x	x	x
Remote headlight control		x	x	
Panic alarm		x	x	x
Silent mode		x	x	x
Car Finder		x	x	x
Vehicle provides audible & visual command confirmation		x	x	x
2-way communication				x
Remote Start				
Remote start	x	x	x	x
Diesel mode	x	x	x	x
Selectable run times	15 or 30 min	15 or 30 min	15 or 30 min	12, 24 or 60 min
Quick Stop option	x	x	x	x
Low voltage check	x	x	x	x
Cold Start		x	x	x
Daily Start		x	x	x
Timer Mode (starts engine every 3 hours)				x
Short Run/Turbo timer				x
Starter anti-grind circuitry	x	x	x	x
Alarm Features				
3-zone alarm system (door trigger, hood & ignition)			x	6-zone
Starter disable			x	x
Passive/active arming			x	x
Auto rearm			x	x
Nuisance prevention circuit NPC			x	x
Alarm zone bypass			x	x
Included shock sensor				Stinger® DoubleGuard®
Multitone siren included				x
Keyless Entry				
Keyless entry outputs			x	x
Ignition controlled door locks			x	x
1 auxiliary output/trunk pop		x	x	4 auxiliary outputs
Daytime Running Lights	x	x	x	
Other				
Limited Life Time Warranty	x	x	x	x